



**CE Marking of Mirrors from silver-coated float glass for internal use
EN 1036-2:2008
Declaration of performances
Mirox MNGE Clear**



We

**AGC Glass Europe
Building Division**


Avenue Jean Monnet 4 - 1348 Louvain-la-Neuve - Belgium
Tel.: +32 - (0) 2 409.30.00 - Fax: +32 - (0) 2 672.44.62

Declare, under his sole responsibility, the following characteristics for the CE Marking of the glass products named **Mirox MNGE Clear**, intended to be used in buildings and construction works, following **EN 1036-2:2008**

NB 0074 0336 0402 0432 0474 0497 0589 0620 0672 0679 0749 0757 0761 0833 1080 1121 1136 1154 1173 1174 1234 1314 1322 1343 1390 1391 1394 1396 1488 1643 1694 1717 1750 1812 2531

	Mirox MNGE Clear characteristics in :	AVCP Systems	2 mm	3 mm	4 mm	5 mm	6 mm	8 mm
1.	Resistance to fire (EN 13501-2)	1	NPD	NPD	NPD	NPD	NPD	NPD
2.	Reaction to fire (EN 13501-1)	3, 4	A1	A1	A1	A1	A1	A1
3.	External fire performances	3, 4	NPD	NPD	NPD	NPD	NPD	NPD
4.	Bullet resistance (EN 1063)	1	NPD	NPD	NPD	NPD	NPD	NPD
5.	Explosion resistance (EN 13541)	1	NPD	NPD	NPD	NPD	NPD	NPD
6.	Burglar resistance (EN 356)	3	NPD	NPD	NPD	NPD	NPD	NPD
7.	Pendulum body impact resistance (EN 12600)	3	NPD	NPD	NPD	NPD	NPD	NPD
8.	Resistance against sudden temperature change and temperature differentials	4	NPD	NPD	NPD	NPD	NPD	NPD
9.	Wind, snow, permanent and imposed load resistance	4	NPD	NPD	NPD	NPD	NPD	NPD
10.	Direct airborne sound reduction (EN 12758): R_w (C;Ctr)	3	NPD	NPD	NPD	NPD	NPD	NPD
11.	U-value (EN 673)	3	5,8	5,8	5,8	5,8	5,7	5,7
12.	Light transmission/reflection (EN 410): $\tau_v / \rho_v / \rho'_v$	3	NPD	NPD	NPD	NPD	NPD	NPD
13.	- Solar transmission/reflection (EN 410): $\tau_e / \rho_e / \rho'_e$ - Solar factor: g	3	NPD NPD	NPD NPD	NPD NPD	NPD NPD	NPD NPD	NPD NPD
14.	Durability	3	PASS	PASS	PASS	PASS	PASS	PASS

Louvain-la-Neuve
23rd of February 2015


 E. Ceriani
 Primary Sales & Strategic, Marketing Director, Building